

CONDENSED SPEC SHEET*

Grade Name: ANTI-FUNGAL SOAP WRAP

Paper coated with special fungicide chemical that replaces LDPE coated paper used in soap wraps.

SUBSTANCE (GSM)	CALIPER (μM)
100	126
115	145
120	151
130	164
TOL : ± 5%	± 5%

PARAMETER	UNITS	VALUE
TEAR FACTOR	-	60 MIN
COBB		
TOP SIDE	GSM	25 MAX
WIRE SIDE		25 MAX
BREAKING LENGTH		
MD	Mtr	7000 MIN
CD		4000 MIN
WET TENSILE		
MD	Mtr	2000 MIN
CD		1000 MIN
MOISTURE	%	5.0 - 6.0
BRIGHTNESS	%	84 (-2)
OPACITY	%	82 (-2)
WAX PICK		
TOP SIDE	NO	15A MIN
WIRE SIDE		15A MIN
ROUGHNESS (BENDTSEN)		
TOP SIDE	ml/min	250 MAX
WIRE SIDE		350 MAX

CONSTRUCTION

	Surface Sized
	Bleached Chemical Pulp
	Surface Sized

Note:

1. All Properties are according to ITC PSPD Measurements
2. Test Climate 23°C/50%RH (Conditioning as per Tappi T 402 sp-98)
3. Tolerances are based upon 95% Confidence limits of single mill measurements of conditioned random samples



FMCG