

EcoTrue Liner is specifically designed for top-liner applications in corrugated boxes, offering a premium white surface that enhances branding and visual appeal. It provides an easy upgrade from traditional brown corrugated cartons, adding a touch of sophistication to packaging. With excellent compatibility across all corrugation machines, **EcoTrue Liner** ensures seamless performance and reliability. Its lightweight design and pigment-coated surface make it an ideal choice for high-quality top-liner solutions.

Specifications

Substance (GSM)	Caliper (μm)	Bending Resistance(L&W) mN		
Tappi T 410	Tappi T 411	Tappi T 556		
		MD	CD	GM
180	243	72	30	46
190	257	85	35	55
200	270	99	41	64
210	284	115	48	74
220	297	132	55	85
230	311	151	63	98
240	324	172	72	111
250	345	194	81	125
260	359	219	90	140
270	373	245	100	157
280	386	255	105	164
290	400	283	117	182
300	420	302	124	194
320	448	366	151	235
TOL: +-4%	+-5%			-15%

Parameter	Units	Value
Ply Bond (Avg.) QC/SOP/101, Tappi T 569	J/m ²	150 Min
Roughness PPS (Avg.) TOP GSM ≤ 300 GSM > 300 QC/SOP/102, Tappi T 555	μm	6.0 Max 8.0 Max
Brightness ISO(with UV-100%) TOP QC/SOP/110, ISO 2470	%	70 Min
Moisture GSM ≤ 300 GSM > 300 QC/SOP/99, Tappi T 412	%	7.0 ± 1.0 8.0 ± 1.0
COBB (60 sec) TOP BOT QC/SOP/100, Tappi T 441	g/m ²	50 Max 100 Max

Construction



Note:

1. All properties are according to ITC Limited, PSPD Unit Kovai measurements
2. Tolerances are based upon 95% confidence limits of single mill measurements of conditioned random samples
3. The specifications in this folder are subject to change. For latest specifications, contact marketing.itcpspd@itc.in



Product can be supplied with FSC® Certification on request.